ELECTRICAL SAFETY SOLUTIONS

Pyro Safety Switches

Prevention in milliseconds to avoid short-circuits, fire ignition and battery draining.

Pyro Safety Switch PSS-4 500V 600J

Autoliv's industry-standard Pyro Safety Switches comply with the high-quality requirements of the vehicle industry. Our Pyro Safety Switches offer a range of technical specifications, including different voltages, short circuit resistance and maximum current.



- Maximum continuous current 500 A
- Non-reversible device
- Suitable for voltage levels up to 600 VDC
- High peak current carrying capability up to 25 000 A
- No ionizing gases / No particles exhaust
- Material Flammability : V0

Product specifications

Maximum switching capacity	With Cpk 600J
Systems configurations tested (Other request, Contact us)	500 V / 10 000 A / 12 µH

Current carrying capacity

Customer cooling system must guarantee the temperature at terminals' connection point does not exceed +125°C

Customers applications examples (Load cable 70 mm² min)	105°C Max, 350 A DC 85°C Max, 420 A DC 50°C Max, 500 A DC
Maximum pulse current	25 000 A / 5 ms

Busbar

Raw-material (base)	CuSn 0,15
Plating material (lead-free)	Sn/Ni
Cross-section	60 mm² or 78 mm²
Busbar resistance (at RT)	
before ops.	≤ 0,05 mΩ
after ops	≥ 50 MΩ / 500 V

Operation time

Operating time	With Cpk 1,67 < 2 ms
450 V / 10kA / 20 µH	Typical 0.8 ms

Triggering conditions acc. to AK-LV 16 & USCAR

Ohmic resistance	≥1,7 Ω and ≤ 2,5 Ω
Current pulse	1,75 A / 0,5 ms Or 1,20 A / 2,0 ms
Pulse slope	> 8 mA / µs
No-triggering current	≤ 0,4 A Or ≤ 5,0 A / ≤ 4 µs
Diagnostic current:	< 100 mA

Temperatures

Operating	-40°C... + 105°C
Environmental	-40°C... + 105°C
Storage	-40°C... + 65°C

Validations


Vibration resistance	AK-LV 124
Mech. Shock resistance	AK-LV 124
Temperature cycle resistance	AK-LV 124
Chemical loads resistance	AK-LV 124
HV-LV resistance before/after ops.	≥ 1 GΩ / 500 V


Terminal type


HV	M6 (Standard) or M8 (Option)
Triggering	AK-2 (Standard) or ABX-5 (Option)
Weight	≤ 125 g

Technical Data and Dimensions

Performance & Dimensions







We refer emphatically to the fact, that all details mentioned, especially the application and utilization recommendation for the products and their system accessories, have been developed under normal conditions, and based on our knowledge and experience. Appropriate storage and usage of the products are assumed. A warranty or reliability of a finished project cannot be deduced because of varying materials, substrates and differing work conditions, neither by any indications nor from verbal statements, irrespective of any legal positions. For the possible accusation that FDT acted intentionally or grossly negligent, the user has to supply evidence that they provided Autoliv with all information and details necessary for an appropriate and correctevaluation through Autoliv in written form, immediately available and complete. The user is responsible for ensuring that the products are suitable for the given application. It is Autoliv's right to change product specifications without notice. Property rights of third parties are to be considered. In addition our particular sales and delivery terms are valid. The latest version of our product data sheet is obligatory, which can be requested directly through Autoliv. All information as well as all technical and drawing data comply with current technical standards and are based on our experience. National standards and regulations must be observed. Technical changes reserved. As of January 2016. © 2016

Read more

autoliv.com